

Edwards Audio

User manual MM1

Thank you for purchasing an Edwards audio phono stage, with care over the correct installation we are sure that it will give many years of pleasure.

INSTALLATION

The main MM1 should be placed on a separate shelf next to or near your Turntable. Connect your turntables arm leads to the sockets marked 'input' observing Red for RIGHT and White/Black for LEFT. If you have an additional Earth or Ground cable attach this to the GND terminal provided above the input sockets. Depending on your systems grounding arrangements it may or may not be necessary to connect this, so if you can hear a hum through your speakers try connecting/disconnecting this wire. Next connect an additional pair of high quality RCA Phono cables between the output sockets and any available LINE input on your amplifier, this is usually marked AUX. The Power supply should be plugged in to any available AC outlet near to your system then plug the Mini Din into the socket marked DC on the rear of the MM1. Please observe the polarity and do not force the plug into the socket else damage may occur. To power 'ON' switch on the AC power supply at the wall, there is no power switch on the phono stage itself.

There are no hard and fast rules as to where to best position the MM1, basically the quieter it is the better it will sound, all you should hear is a feint hiss, if this is on the floor behind your equipment rack the so be it. Don't be worried about where it is, it's position and orientation will have no detrimental effect on the MM1's function or reliability.

FRONT PANEL LED

Should you want to, you can turn off the front panel LED indicator. This is done by moving the Blue jumper shown on as J6 on diagram 2. This is located near the LED at the front of the PCB. This can be accessed by removing the 4 screws on the rear panel marked in black on diagram 1. and Sliding the PCB out backwards, see diagram 1.

LISTENING

Having successfully connected the MM1 to your system you can now try playing a record. Select Aux on your amplifier (or whatever input you used to plug the MM1 into) and slowly advance the volume control, hopefully music will be heard. Assuming all is well, lift the needle from the groove and listen to check that there are no hums or buzzes, if there are, experiment with the position of the MM1 and or the ground connection, it may well be that the quietest position is not on a shelf at all.




Diagram 1

WORLDWIDE GUARANTEE

There are no user serviceable parts inside, so please do not be tempted to play or modify any part of the MM1, as this will invalidate your guarantee. By registering your MM1 via our website www.talkelectronics.com/support your guarantee will be extended to ten years from the date of purchase, free of charge.

This entitles you to have the unit repaired provided that it was originally purchased from an authorised Talk/Edwards Audio dealer or distributor.

The manufacturer can take no responsibility for defects arising from accident, misuse, abuse, wear and tear, neglect or through unauthorised adjustment and/or repair, neither can they accept responsibility for damage or loss occurring during transit to or from the person claiming under the guarantee.

THE WARRANTY COVERS Parts and labour costs for ten years (if registered) two years if not, from the purchase date. After ten years you must pay for both parts and labour costs. The warranty does not cover transportation costs at anytime.

CLAIMS UNDER GUARANTEE

This equipment should be packed in the original packing and returned to the dealer from whom it was purchased, or failing this, directly to the Talk/Edwards Audio distributor in the country of residence. It should be sent carriage prepaid by a reputable carrier – NOT by post. No responsibility can be accepted for the unit whilst in transit to the dealer or distributor and customers are therefore advised to insure the unit against loss or damage whilst in transit.

CONFORMANCE

The Edwards Audio MM1 has been manufactured to conform with the protection requirements of the EC Council directive 89/336/EEC relating to EMC by application of the following standards: EN500811 1997 Emissions Standard. EN500821 1997 Immunity Standard. and also the requirements of the EC low voltage directive relating to electrical safety by application of the following standard: BSEN/IEC60065: 2002 International Safety Standard. For the purposes of testing the MM1 was used with the high quality interconnects supplied by Merlin Cables. Compliance with the above standards may only be made if the unit is installed as per this manual and using the correct cables.

SPECIFICATIONS

Max Input.....	76mV
Nominal Input.....	3mV
Gain.....	36dB
Frequency response.....	10Hz -100K +/- 3dB
THD Distortion.....	<0.02% 1kHz
Signal to noise.....	-76dB / -85db A - weighted
RIAA.....	within 0.5dB
Stereo separation better than	65dB - 20-20kHz
Input Loading.....	47K with 120pF
Output impedance.....	<10 Ohms
Nominal output.....	185.5mV
Max output level	4.7v depending upon input
Dimensions WxHxL.....	114.5mm x 47.5mm x 89mm
Weight.....	0.5kg
Power consumption(Max).....	3.0W

E&OE - we reserve the right to alter and improve the MM1 without prior notice at anytime

PSU

Max output	+/-18V DC
Power consumption (Max)	3W
Voltage.....	115/230v AC*

* Units are supplied with correct PSU for country of destination when originally shipped

All TALK Electronics products are designed and manufactured in the UK using as many locally made parts as possible



Edwards Audio is part of TALK Electronics

3 Eliot Close, Camberley, Surrey GU15 1LW UK

Telephone: 08456 123388 or 07736 421928 Fax: 01276 613250

email: info@talkelectronics.com website: www.talkelectronics.com

Diagram 2

